

ODIE'S[®] OIL

Please read the instructions and safety procedures before proceeding.

Prep:
15 Minutes

Ideal Application:
72 F

Light Use:
Immediately

Full Cure:
1-2 Days

INSTRUCTIONS: Oil, Dark, Wood Butter, Wax, & Dark Wax

Directions:

1. Stir Odie's Oil or Odie's Dark to mix settled ingredients, other Odie's products do not need stirring.
2. Apply Odie's product with a non-woven pad and rub the product on the surface. This will cause friction and help the wood fiber to draw in more products. Rub vigorously, but don't overdo it with the amount applied. Check the piece multiple times to ensure the piece still has oil on top. If you see dry spots apply more oil.
3. After application, allow the oil to set for 10 minutes to 3 hours. The time given depends on the surface it was applied to and how much was applied. You can wait a little bit longer, but the ability to buff the product off will be tougher. **DO NOT EXCEED 12 HOURS.**
4. Once the allowed time has passed, take a terry (100% cotton) cloth towel and proceed to buff off **ALL** of the product from the surface. When the towel is full of product, switch to a new and clean terry cloth. Buff the surface until the entire surface is clean and no product remains. If you can swipe a finger across the surface and not make a mark, you are finished!
5. Clean off all tools with a rag. Submerge all oiled rags and oil-soaked materials into the water overnight. Hang to dry outside in a safe place before proper disposal. Read all safety instructions from Odie's Oil for proper care and disposal.
6. The finished piece can be used almost immediately after buffing is completed, but giving the product 1-2 days to cure before use is ideal. If the piece is going to be exposed to any liquids **WAIT TWO WEEKS OF CURE TIME.**
7. If more coats of the product are desired, they can be applied using the same steps after 24 hours of curing.

Notes:

- For repairs or maintenance, 10 hours of cure time is suggested before the use of the product after reapplication.
- For Epoxy and Resin projects, it is recommended to use less oil on the wood and epoxy surfaces.
- Wash immediately after using your piece with food. Can be submerged in water for a short period of time. Wash with water and mild soap that is made for wood that is oiled. Do not put any wood into the dishwasher.

Email: HardwoodSales@AdvantageLumber.com

Phone: 1 (877) 232 - 3915

The opinions given here are strictly the opinions of Advantage Lumber, LLC and WoodSlabs.com and not necessarily the views of any of the listed products. All opinions are our own and are solely from our experiences. These pages are subject to change. Customers should take the time to read the instructions and safety precautions from each product before using any materials.



Please read the instructions and safety procedures before proceeding.

Product Explanations:

Odie's Oil This is a food-safe, solvent-free, and waterproof wood finish and stabilizer. It can be applied for interior and exterior usage. It contains natural UV inhibitors.

Odie's Dark This is a food-safe and solvent-free wood finish and stabilizer. It contains natural oxidizing oils that will darken the wood when applied and as it ages. Applied for interior usage.

Odie's Wood Butter This is a food-safe and solvent-free wood finish and stabilizer. Can be used for all species. It can be used on new wood and is suitable to use over other finishes to renew.

Odie's Wax This is a highly concentrated hard wax used for woods that are lighter in color. Used when a major color change is not desired. Food-safe and contains non-toxic solvent.

Odie's Dark Wax This is a food-safe and solvent-free hard wax. It contains natural oxidizing oils that will darken the wood when applied and as it ages. Applied for interior usage.

Odie's Super Penetrating Oil This is a thinner version of Odie's oil. It is meant to thin out Odie's oil to achieve the desired consistency. It is non-toxic.

Odie's Super Cleaning This is a powerful cleaner and degreaser made out of a blend of citrus extracts and plant-derived surfactants.

Odie's Safer Solvent This is an all-natural food-grade citrus solvent. It is a non-toxic cleaner that is used to clean and prepare surfaces for finishing.

Notes:

- Reminder Rags and oil-soaked materials are highly flammable and can self-combust as the product evaporates **regardless of air temperature**. Place rags in water overnight then hang them to dry outside in a safe location, once dry discard the rags properly.

Email: HardwoodSales@AdvantageLumber.com

Phone: 1 (877) 232 - 3915

The opinions given here are strictly the opinions of Advantage Lumber, LLC and WoodSlabs.com and not necessarily the views of any of the listed products. All opinions are our own and are solely from our experiences. These pages are subject to change. Customers should take the time to read the instructions and safety precautions from each product before using any materials.